

Free Standing Water Dispenser



- ▶ Hot, Normal and Cold Water
- ▶ Bottom Loading Design
- ▶ Stainless Steel Water Tank
- ▶ High Efficiency Compressor Cooling
- ▶ Hot Water Capacity: 5l/h
- ▶ Cold Water Capacity: 2l/h
- ▶ Double Safety Protection For Low Water
- ▶ Child Safety Lock

SGL2020BM

Specifications

Taps	3 Buttons
Hot / Cold / Normal	Yes / Yes / Yes
Tank	Stainless Steel
Refrigerant Type	R134a
Voltage (V, Hz)	220-240V / 50Hz
Dimension (Prod/Pack HxWxD mm)	1062x339x358 / 1120x385x400
Weight (Net /Gross Kg)	17 / 19
Stuffing (40HC units)	405



- ▶ Hot, Normal & Cold Water
- ▶ 3.6l Big Cold Tank
- ▶ Cooling Capacity: 4L/Hr
- ▶ Heating Capacity : 5L/Hr
- ▶ Luxury Touch Button Design
- ▶ Stainless Steel Water Tank
- ▶ 16L Cabinet
- ▶ Double Safety Protection For Low Water

SGL2871

Specifications

Taps	3 Buttons (touch buttons)
Child safety lock	Yes
Hot / Cold / Normal	Yes / Yes / Yes
Tank	Stainless Steel
Refrigerant Type	R134a
Voltage (V, Hz)	220-240V / 50Hz
Dimension (Prod/Pack HxWxD Mm)	1012x310x335 / 1044x372x393
Weight (Net /Gross Kg)	14.3/16.1
Stuffing (40HC units)	450



- ▶ Premium Elegant Korean Design
- ▶ Stainless Steel Water Tank
- ▶ High Efficiency Korean Compressor
- ▶ Hot water safety faucet
- ▶ Child Lock
- ▶ Double safety protection

SGL2171K

Specifications

Taps	2 Taps
Hot/Cold/Normal	Yes / Yes / No
Tank	Stainless Steel
Refrigerant type	R134a
Voltage(V,Hz)	220-240V / 50Hz
Dimension(prod/Pack	990 x 300 x 320 / 1020 x 310 x 330
Weight	20 /21
Stuffing (40HC units)	550



SGL8900K

Specification

Taps	2 Taps
Special Feature	Super Slim Design, Safety Water Tap, Child-Lock
Hot / Cold / Normal	Yes / Yes / No
Tank	Stainless Steel
Refrigerant Type	R134A
Voltage (V, Hz)	220-240V, 50-60Hz
Dimension (Prod/Pack HxWxD mm)	1170x255 x 482 / 1230x315 x 535
Weight (Net /Gross Kg)	19 / 22
Stuffing (20'/40'/40"HC Units)	81 / 164 / 327



SGL1051

Specifications

Taps	3 Taps
Special Feature	Slim Design, Safety Water Tap, Child-Lock
Hot / Cold / Normal	Yes / Yes / Yes
Tank	Stainless Steel
Refrigerant Type	R134a
Voltage (V, Hz)	220-240V / 50Hz
Dimension (Prod/Pack HxWxD mm)	940x310x345 / 990x330x350
Weight (Net /Gross Kg)	16.00/17.70
Stuffing (40"HC Units)	630



SGL1171

Specifications

Taps	2 Taps
Special Feature	With Paper Cup Holder
Hot / Cold / Normal	Yes / Yes / No
Tank	Stainless Steel
Refrigerant Type	R134a
Voltage (V, Hz)	220-240V, 50/60Hz
Dimension (Prod/Pack HxWxD mm)	960x312x325 / 998x375x365
Weight (Net /Gross Kg)	13/14
Stuffing (40"HC Units)	450



SGL1191 WITH REFRIGERATOR

Specifications

Taps	2 Taps
Special Feature	With Paper Cup Holder
Hot / Cold / Normal	Yes / Yes / No
Tank	Stainless Steel
Refrigerant Type	R134a
Voltage (V, Hz)	220-240V 50/60Hz
Dimension (Prod/Pack HxWxD mm)	960x312x325 / 998x375x365
Weight (Net /Gross Kg)	13/15
Stuffing (40"HC Units)	450

Free Standing Water Dispenser



WITH REFRIGERATOR

WITH CABINET

SGL1891 / SGL1871

Specifications

Body / Taps	2 Taps
Special Feature	With Paper Cup Holder
Hot / Cold / Normal	Yes / Yes / No
Tank	Stainless Steel
Refrigerant Type	R134a
Voltage (V, Hz)	220-240V, 50/60Hz
Dimension (Prod/Pack HxWxD mm)	960x312x325 / 998x375x365
Weight (Net /Gross Kg)	15/16 - 14/15
Stuffing (40'HC Units)	440



SGL2271

Specifications

Body / Taps	3 Taps
Special Feature	Elegant Design with Child Lock
Hot / Cold / Normal	Yes/Yes/Yes
Tank	Stainless Steel
Refrigerant Type	R134A
Voltage (V, Hz)	220-240V, 50-60Hz
Dimension (Prod/Pack HxWxD mm)	310x362x990
Weight (Net /Gross Kg)	13.3/15.2
Stuffing (20'/40'/40'HC Units)	192/396/450



SGL1131

Specifications

Taps	2 Taps
Special Feature	With Paper Cup Holder
Hot / Cold / Normal	Yes / Yes / No
Tank	Stainless Steel
Refrigerant Type	R134a
Voltage (V, Hz)	220-240V 50/60Hz
Dimension (Prod/Pack HxWxD mm)	510x312x325 / 555x375x365
Weight (Net /Gross Kg)	9/10
Stuffing (40'HC Units)	890



SGL1831

Specifications

Taps	2 Taps
Special Feature	With Paper Cup Holder
Hot / Cold / Normal	Yes / Yes / No
Tank	Stainless Steel
Refrigerant Type	R134a
Voltage (V, Hz)	220-240V, 50/60Hz
Dimension (Prod/Pack HxWxD mm)	510x312x325 / 555x375x365
Weight (Net /Gross Kg)	12.3/13.7
Stuffing (40'HC Units)	880

Stainless Steel Water Coolers



SGCL25T2

Specifications

Gross Capacity (US Gallon)/hour	22 USG/HR
Body	430 BA
Taps/Purifier	2 / Yes
Temperature Range	+5° C TO +10°C
Horse Power (HP)	1/4
Refrigerant Type	R134a
Voltage (V, Hz)	220-240V, 50Hz
Dimension (Prod HxWxD mm)	1290x610x530
Weight (Net /Gross Kg)	30/32



SGCL32T2

Specifications

Gross Capacity (US Gallon)/hour	25 USG/HR
Body	430 BA
Taps/Purifier	2 / Yes
Temperature Range	+5° C TO + 10°C
Horse Power (HP)	1/4
Refrigerant Type	R134a
Voltage (V, Hz)	220-240V, 50Hz
Dimension (Prod HxWxD mm)	1270x580x590
Weight (Net /Gross Kg)	35/37



SGCL50T3

Specifications

Gross Capacity (US Gallon)/hour	45 USG/HR
Body	430 BA
Taps/Purifier	3 / Yes
Temperature Range	+5° C TO +10°C
Horse Power (HP)	1/3
Refrigerant Type	R134a
Voltage (V, Hz)	220-240V, 50Hz
Dimension (Prod HxWxD mm)	1270x640x590
Weight (Net /Gross Kg)	43/45



SGCL80T3

Specifications

Gross Capacity (US Gallon)/hour	70 USG/HR
Body	430 BA
Taps/Purifier	3 / Yes
Temperature Range	+5° C TO +10°C
Horse Power (HP)	3/8
Refrigerant Type	R134a
Voltage (V, Hz)	220-240V, 50Hz
Dimension (Prod HxWxD mm)	1270x750x590
Weight (Net /Gross Kg)	51/55

Stainless Steel Water Coolers



SGCL95T4

Specifications

Gross Capacity (US Gallon)/hour	85 USG/HR
Body	430 BA
Taps/Purifier	4 / Yes
Temperature Range	+5° C TO +10°C
Horse Power (HP)	1/2
Refrigerant Type	R134a
Voltage (V, Hz)	220-240V, 50Hz
Dimension (Prod HxWxD mm)	1270x930x610
Weight (Net /Gross Kg)	58/60



SGCL120T4

Specifications

Gross Capacity (US Gallon)/hour	100 USG/HR
Body	430 BA
Taps/Purifier	4 / Yes
Temperature Range	+5° C TO +10°C
Horse Power (HP)	3/4
Purifier	Yes
Refrigerant Type	R134a
Voltage (V, Hz)	220-240V, 50Hz
Dimension (Prod HxWxD mm)	1270x1080x610
Weight (Net /Gross Kg)	65 / 67



SGCL125T5

Specifications

Gross Capacity (US Gallon)/hour	125 USG/HR
Body	430 BA
Taps/Purifier	5 / Yes
Temperature Range	+5° C TO +10°C
Horse Power (HP)	3/4
Refrigerant Type	R134a
Voltage (V, Hz)	220-240V, 50Hz
Dimension (Prod HxWxD mm)	1270x1080x690
Weight (Net /Gross Kg)	72 / 74



SGAA26T2

Specifications

Gross Capacity (US Gallon)/hour	20 Gallon Per Hour
Body	430 BA
Taps/Purifier	2 / Yes
Temperature Range	+5° C TO +10°C
Horse Power (HP)	1/5
Refrigerant Type	R134a
Voltage (V, Hz)	220V, 50Hz
Dimension (Prod/Pack HxWxD mm)	1240x505x415
Weight (Net /Gross Kg)	35.50 / 36.25



SGAA33T2

Specifications

Gross Capacity (US Gallon)/hour	25 Gallon Per Hour
Body	430 BA
Taps/Purifier	2 / Yes
Temperature Range	+5° C TO +10°C
Horse Power (HP)	1/5
Refrigerant Type	R134a
Voltage (V, Hz)	220V, 50Hz
Dimension (Prod HxWxD mm)	1240x545x415
Weight (Net /Gross Kg)	36.25 / 37.80



SGAA52T3

Specifications

Gross Capacity (US Gallon)/hour	45 Gallon Per Hour
Body	430 BA
Taps/Purifier	3 / Yes
Temperature Range	+5° C TO +10°C
Horse Power (HP)	1/4
Refrigerant Type	R134a
Voltage (V, Hz)	220V, 50Hz
Dimension (Prod HxWxD mm)	1240x615x415
Weight (Net /Gross Kg)	37.25 / 38.50



SGAA76T3

Specifications

Gross Capacity (US Gallon)/hour	70 Gallon Per Hour
Body	430 BA
Taps/Purifier	3 / Yes
Temperature Range	+5° C TO +10°C
Horse Power (HP)	1/3
Refrigerant Type	R134a
Voltage (V, Hz)	220V, 50 Hz
Dimension (Prod HxWxD mm)	1240x750x415
Weight (Net /Gross Kg)	44.60 / 45.80



SGAA92T4

Specifications

Gross Capacity (US Gallon)/hour	85 Gallon Per Hour
Body	430 BA
Taps/Purifier	4 / Yes
Temperature Range	+5° C TO +10°C
Horse Power (HP)	3/8
Refrigerant Type	R134a
Voltage (V, Hz)	220V, 50 Hz
Dimension (Prod HxWxD mm)	1240x900x415
Weight (Net /Gross Kg)	48.25 /49.75

Stainless Steel Water Coolers



SGAA110T5

Specifications

Gross Capacity (US Gallon)/hour	100 Gallon Per Hour
Body	430 BA
Taps/Purifier	5 / Yes
Temperature Range	+5° C TO +10°C
Horse Power (HP)	3/8
Refrigerant Type	R134a
Voltage (V, Hz)	220V, 50Hz
Dimension (Prod HxWxD mm)	1240x1000x415
Weight (Net /Gross Kg)	51.45/ 52.75



SGAA160T5

Specifications

Gross Capacity (US Gallon)/hour	150 Gallon Per Hour
Body	430 BA
Taps/Purifier	5 / Yes
Temperature Range	+5° C TO +10°C
Horse Power (HP)	3/4
Refrigerant Type	R134a
Voltage (V, Hz)	220-240V, 50Hz
Dimension (Prod HxWxD mm)	1520x1120x700
Weight (Net /Gross Kg)	90.50/ 91.75



SGAA161T5BSQ

Specifications

Gross Capacity (US Gallon)/hour	150 Gallon Per Hour
Body	201 BF
Taps/Purifier	5 / Yes
Temperature Range	+5° C TO +10°C
Horse Power (HP)	1
Refrigerant Type	R134a
Voltage (V, Hz)	220-240 V, 50Hz
Dimension (Prod HxWxD mm)	1520x1120x700
Weight (Net /Gross Kg)	90.50 / 91.75

Small Home Appliances

